
Desso Textile floor covering - Tiles

Salt

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1	I/10 "						
Aspect	ISO 2424		Loop pil	е						
Dye method			Solution	dyed						
Dimensions	EN 994	cm x cm	50 x 50 / 19,68" x 19,68" (20 tiles per box)							
Primary backing	ISO 2424		Polyeste	er fleece						
Secondary backing	ISO 2424		Desso ProBase Polyver® - Polyscan®							
Pile fibre composition	ISO 2424		BCF Polyamide 6 and ECONYL® (ECONYL® is made from 100% regenerated content) **							
Total thickness	ISO 1765	mm	7.0		inch	0.3				
Effective pile thickness	ISO 1766	mm	3.2		inch	0.13				
Total mass	ISO 8543	g/m²	4200		oz/yd²	124.0				
Total pile mass	ISO 2424	g/m²	655		oz/yd²	19.3		-		
Effective pile mass	ISO 8543	g/m²	390		oz/yd²	11.5				
Pile density	ISO 8543	g/cm³	0.122		lb/in³	0.0044				
Number of tufts	ISO 1763	/dm²	1540		/yd²	128759		-		
Stroll test	ISO 6356	kV	≤ 2,0							
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10)9						
Horizontal resistance	ISO 10965	Ohm	-							
Use classification	EN 1307		33 Commercial - heavy use							
Luxury rating	EN 1307		LC 1							
Dimensional stability	EN 986	%	≤ 0,2							
Impact sound reduction ΔL _w	ISO 10140	dB	-							
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000		
		$\alpha_{\rm s}$	-	-	-	-	-	-		
Noise reduction	ISO 354	$\alpha_{_{w}}$	-							
Thermal resistance	ISO 8302	m².K/W	≤ 0,17							
Flammability	EN 13501-1	EN 13501-1		Bfl - s1 (loose laid tested)						
Prodis - GUT	www.pro-dis.	www.pro-dis.info								







^{**} ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.desso.com.

Desso flooring products are to be installed in full accordance with Desso's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Desso flooring products should only be used as floorcoverings. Note: Desso reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www. desso.com

EN-20150519

